



TEST REPORT

Technical Report: (5325)308-0065

November 06, 2025

Date Received: November 04, 2025

Page 1 of 5

ELKY CONSTRUCTION PTE LTD
10 ADMIRALTY STREET #03-51,
NORTHLINK BUILDING,
SINGAPORE 757695

Sample Description: Sample(s) received are stated to be:
ELKY E-138

Product End Use:	Contact Adhesive	Age Group:	/
Color:	/	Order #:	/
Country of Origin:	/	Country of Destination:	/
Product Reference:	/	Retest No.:	/
Overall Conclusion:	PASS	P.O. No.:	/

Bureau Veritas Singapore Pte Ltd
37A, Tampines Street 92,
#06-01, Singapore 528886
Tel: 65-62838366 Fax: 65-62838966
website: www.bureauveritas.com/cps

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://cps.bureauveritas.com> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

The content of this PDF file is in accordance with the original issued reports for reference only.
This Test Report cannot be reproduced, except in full, without prior written permission of the company.

SUMMARY OF TEST RESULTS

TEST REQUESTED	CONCLUSION	REMARK
Free and Hydrolyzed Formaldehyde Content – ISO 14184-1	PASS	/
Free and Hydrolyzed Formaldehyde Content – ISO 17226-2	PASS	/

REMARK

If there are questions or concerns on this report, please contact the following persons:

General enquiry and invoicing

Customer Service, (65) 62838366
Email: customer.enquiry@sg.bureauveritas.com

Technical enquiry-Chemical

Jeffrey Lee, (65) 62838366
Email: jeffrey.lee@sg.bureauveritas.com
Wang Ya Nan, (65) 62838366
Email: ya-nan.wang@sg.bureauveritas.com

BUREAU VERITAS SINGAPORE PTE. LTD.



Jeffrey Lee Boon Chek
Analytical Laboratory Manager

Photo of the Submitted Sample



Sample Description Assigned by Laboratory:

Test Item	Description	Client Claimed Material
I001	ELKY E-138	Contact Adhesive

TEST RESULT

Free and Hydrolyzed Formaldehyde Content

Test Method : ISO 14184-1:2011

Maximum Limit:	Not Detected^[a]		
Tested Item(s)	Result		Conclusion
	Conc.	Unit	
I001	< 10	mg/kg	PASS

Note:

ND = Not detected

">" = Less than

Conc. = Concentration

mg/kg = milligram per kilogram

Detection Limit (mg/kg): 10

Remark :

- Result(s) was (were) reported from the average of two trials.
- [a] denotes this maximum allowable limit is provided by client

TEST RESULT

Free and Hydrolyzed Formaldehyde Content

Test Method : ISO 17226-2:2018

Maximum Limit:	Not Detected^[a]		
Tested Item(s)	Result		Conclusion
	Conc.	Unit	
I001	< 10	mg/kg	PASS

Note:

ND = Not detected

"<" = Less than

Conc. = Concentration

mg/kg = milligram per kilogram

Detection Limit (mg/kg): 10

Remark :

- ^[a] denotes this maximum allowable limit is provided by client

END

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

Section 1: Identification Of The Hazardous Chemical And Of The Supplier	Bahagian 1: Pengenalpastian Produk Kimia Dan Syarikat Pembekal
Identification Of Chemical : ELKY E-138 Supplier : ELKY CONSTRUCTION PTE LTD Address: 10 Admiralty Street #03-51 Singapore 757695	Pengenalalan Bahan Kimia : ELKY E-138 Pembekal : ELKY CONSTRUCTION PTE LTD Alamat: 10 Admiralty Street #03-51 Singapore 757695
Section 2: Hazard Identification	Bahagian 2: Pengenalalan Bahaya
<u>GHS CLASSIFICATION</u> Physical Hazard : Flam. Liq 2 Health Hazard : Acute Toxicity Oral (LD50) Rat, Category 4 Skin Irrit 2 Repr. 2 STOT SE3 STOT RE2 Asp. Haz. Environment Hazard : Not Classified <u>GHS LABEL</u>  Signal Word : DANGER Hazard Hazard Statement: H225: Highly flammable liquid and vapour H302: Harmful if swallowed H304: May be fatal if swallowed and enter airways H315: Causes skin irritation H335: May cause respiratory irritation H336: May cause drowsiness or dizziness H361: Suspected of damaging fertility or the unborn child H373: May cause damage to kidney, central nervous system, Liver and brain if through prolonged or repeated exposure	<u>KLASIFIKASI GHS</u> Bahaya Fizikal : Flam. Liq 2 Bahaya Kesihatan : Acute Toxicity Oral (LD50) Rat, Category 4 Skin Irrit 2 Repr. 2 STOT SE3 STOT RE3 Asp. Haz. Bahaya Alam Sekitar : Tiada Klasifikasi <u>LABEL GHS</u>  Perkataan Amaran: Bahaya Penyata Pernyataan Bahaya: H225: Cecair dan wap yang sangat mudah terbakar H302: Memudaratkan jika tertelan H304: Boleh menyebabkan kematian jika tertelan atau memasuki saluran udara H315: Menyebabkan kerengsaan kulit H335: Boleh menyebabkan kerengsaan pernafasan H336: Disyaki merosakkan kesuburan atau janin H373: Boleh menyebabkan kerosakan buah pinggang, system saraf tunjang hati dan otak melalui pendedahan berpanjangan atau berulang

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

Precaution Statements(s): P201: Obtain special instruction before use P202: Do not handle until all safety precautions have been read and understood P210: Keep away from heat/spark/open flames/hot surfaces –no smoking P233: Keep container tightly closed P241: Use explosion-proof electrical/ventilating/lighting Equipment P242: Use only non-sparking tools P243: Take precautionary measures against static discharge P261: Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray P264: Wash thoroughly after handling P271: Use only outdoors or in a well-ventilated area P260: Do not breathe dust/fume/gas/mist/ vapours/ spray P273: Avoid release to the environment P280: Wear protective gloves/protective clothing/eye protection/face protection P281: Use personal protective equipment as required P312: Call a POISON CENTER or doctor if you feel unwell P314: Do not induce vomiting P361: Remove / Take off immediately all contaminated clothing P403: Store in a well-ventilated place			Penyata Amaran: P201: Dapatkan arahan sebelum guna P202: Jangan guna sehingga semua langkah keselamatan telah dibaca dan difahami P210: Jauhkan dari haba/percikan/api/permukaan panas –Jangan merokok P233: Tutup bekas dengan ketat P241: Gunakan elektrik kalis letupan/pengudaraan/ peralatan pengcahayaan P242: Hanya gunakan alat yang tidak memercikkan api P243: Ambil langkah berjaga-jaga terhadap pelepasan Static P261: Elakkan daripada menghidu habuk/wasap/gas/ kabut/ wap/semburan P264: Basuh bersih-bersih selepas mengendalikan P201: Dapatkan arahan khas lain sebelum digunakan P271: Gunakan hanya di luar atau di kawasan pengudaraan yang baik P273: Elakkan pelepasan ke persekitaran P280: Pakai sarung tangan pelindung/pakaian pelindung/ perlindungan mata/pelindung muka P281: Gunakan peralatan perlindungan diri seperti yang diperlukan P312: Hubungi pusat keracunan atau doctor jika tidak sihat P314: Dapatkan rawatan kesihatan jika tidak sihat P331: Jangan muntahkan secara paksa P361: Buka pakaian yang dicemari P403: Simpan di tempat yang mempunyai pengudaraan baik		
Section 3: Composition and Information on Ingredients			Bahagian 3: Komposisi dan Maklumat Bahan		
Chemical Name	CAS No.	Composition (%)	Nama Bahan Kimia	CAS No.	Komposisi (%)
Toluene	108-88-3	> 30	Tolin	108-88-3	> 30
Chlorinated Hydrocarbons	63449-39-8	> 30	Hidrokarbon Beklorin	63449-39-8	> 30
Synthetic Polymer	126-99-88	> 10	Polimer Sintetik	126-99-88	> 10
Petroleum Resin	9003-35-4	> 10	Petroleum Resin	9003-35-4	> 10
Section 4: First-aid Measures			Bahagian 4: Langkah-langkah Pertolongan Cemas		
Inhalation Remove to fresh air. Give artificial respiration if not breathing. Oxygen may be given if necessary. If sign and symptom of toxicity persists, seek for medical assistant. Skin Contact Wipe off excess and wash with soap and water. Proprietary skin cleansers may help removal from skin (do not use solvents). Obtain medical advise if skin irritation persists.			Penyedutan Alih ke tempat berudara segar. Beri bantuan pernafasan jika sukar bernafas. Berikan bekalan oksigen jika perlu. Sekiranya ada simptom ketoksikan berterusan, hubungi doctor. Sentuhan Kulit Lap lebihan tumpahan pada kulit dan basuh dengan air dan sabun. Gunakan pencuci kulit yang sesuai (jangan guna solvent). Dapatkan nasihat perubatan jika kulit merengsa.		

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025
Eye Contact Check and remove any contact lenses. Flush eyes with large amount of water until irritation subsides. If irritation persists, get medical attention. Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.		Sentuhan Mata Keluarkan kanta lekak sekiranya ada. Bilas dengan air yang banyak sehingga kerengsaan berkurangan. Sekiranya kerengsaan berterusan, dapatkan rawatan perubatan. Tertelan Jangan muntahkan melainkan mendapat arahan daripada pakar perubatan. Jangan berikan sesuatu melalui mulut kepada mangsa yang pengsan. Sekiranya jumlah bahan yang tertalan adalah banyak, hubungi pakar perubatan secepat mungkin. Longgarkan pakaian mangsa seperti tali kolar, tali leher, tali pinggang dan gelang.	
Section 5: Fire-fighting Measures		Bahagian 5: Langkah-langkah Memadam Kebakaran	
Main Hazard Explosion Specific Hazard Carbon monoxide may evolved if incomplete combustion occurs. Will float and can be reignited on water surface. The vapor is heavier than air, spread along the ground and distant ignition is possible. Extinguishing Media Carbon dioxide, chemical powder, foam and water fog Unsuitable Media Water Jet (the chemical is lighter than water. The burning substance could float on water surface) Fire Fighting Procedure Allow fire to burn down under control or extinguish with foam, chemical powder or carbon dioxide. Try to cover liquid spills with foam. Protective Equipment for Fire Fighter Wear full protective clothing and self-contained breathing apparatus if significant amount are involved.		Bahaya Utama Bahaya letupan Bahaya Khas Pengumpulan Karbon Monoksida boleh terbentuk jika berlaku pembakaran tidak lengkap. Bahan kimia boleh terapung dan terbakar atas permukaan air. Wasap kimia lebih berat daripada udara dan boleh tersebar pada permukaan tanah. Pembakaran boleh tercetus dari jarak jauh. Media Pemadaman Karbon dioksida, serbuk kima, buih dan kabus air. Media Pemadaman Yang Tidak Sesuai Pancutan Air (Bahan kimia lebih ringan daripada air dan boleh terapung atas permukaan air) Langkah-Langkah Memadam Api Biarkan kebakaran turun ke tahap yang boleh dikawal atau padamkan api dengan menggunakan pemadam api buih, serbuk kima atau karbon dioksida. Cuba kawal tumpahan cecair dengan pemadam api buih. Pakaian Keselamatan Untuk Penyelamat Kebakaran Pakai pakaian keselamatan penuh dan juga alat pernafasan yang sesuai sekiranya kebakaran adalah besar.	
Section 6: Accidental Release Measures		Bahagian 6: Langkah-langkah Pelepasan Tidak Sengaja	
Protective Measures Avoid contact with spilled material. Immediately remove all contaminated clothing. Remove all possible sources of ignition in the surrounding area. Prevent spilled material from entering drains, ditches or rivers by using sand, earth or barriers. Attempt to disperse the vapor or to direct its flow to safe location by using fog spray. Refer Section 8 for guidance on selection of Personal Protective Equipment. Refer Section 13 for information on disposal.		Langkah-Langkah Kawalan Elakkan daripada tersentuh dengan bahan tumpahan. Alihkan semua pakaian tercemar dengan bahan tumpahan. Alihkan semua sumber nyalaan yang terdapat disekitar kawasan tumpahan. Elakkan bahan tumpahan daripada memasuki longkang, parit atau sungai berdekatan dengan menggunakan pasir, tanah atau penghadang yang sesuai. Cuba kurangkan ketepuan wap kimia atau alihkannya ke kawasan yang lebih selamat menggunakan semburan kabus air.	

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

Clean Up Method For small quantity (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. For big quantity (> 1 drum), transfer to vacuum truck to a salvage tank for recovery or safe disposal. Allow residue to evaporate or soak up with appropriate absorbent material and dispose of safely Remove contaminated soil and dispose of safely Additional Advise Notify local authorities if any exposure to the general public or the environment occurs or is likely to occur.	Rujuk seksyen 8 untuk rujukan pakaian keselamatan yang sesuai Rujuk seksyen 13 untuk informasi pelupusan yang sesuai. Cara-Cara Pembersihan Untuk kuantiti yang kecil (< 1 drum), alihkan bahan tumpahan ke dalam bekas yang berlabel dan bertutup untuk diproses semula atau untuk pelupusan. Untuk kuantiti yang besar (> 1 drum), alihkan bahan tumpahan ke dalam trak vacuum atau tangki simpanan untuk diproses semula atau untuk pelupusan. Biarkan sisa-sisa tumpahan tersejat atau sejatkan sisa-sisa tersebut dengan bahan penyejatan yang sesuai untuk dilupuskan. Asingkan bahagian tanah yang tercemar dengan bahan tumpahan untuk dilupuskan. Langkah-Langkah Tambahan Umumkan pada penguatkuasa tempatan sekiranya tumpahan yang berlaku boleh mendedahkan bahaya pada masyarakat setempat.
Section 7: Handling and Storage	Bahagian 7: Pengendalian dan Penyimpanan
General Precaution Avoid breathing vapors or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Refer section 8 for selecting suitable protective equipment. Handling Avoid contact with skin, eyes and clothing. Exposure to solvent vapors should be controlled by local exhaust ventilation. Where this is not practicable, suitable respirator must be worn. The solvent vapors are highly flammable and heavier than air. Keep away from sources of ignition, sparks, hot surfaces, electrical equipment and heating appliances. Maintain efficient ventilation using flame proof equipment where necessary. Equipment/machinery should be earthed to prevent static electricity build-up. Storage Must be stored in a diked (bunded) well-ventilated area, away from direct sunlight, ignition sources and other sources of heat. Storage Temperature: Ambient.	Pengawasan Umum Elakkan daripada menghidu wap atau menyentuh bahan ini. Gunakan di kawasan yang mempunyai pengudaraan yang baik. Basuh tangan dan perkakasan setelah habis menggunakannya. Rujukan seksyen 8 untuk rujukan pakaian keselamatan yang sesuai. Pengendalian Elakkan bahan ini daripada tersentuh kulit, mata dan pakaian sewaktu pengendalian. Pendedahan kepada wap kimia perlu dikawal menerusi Pengalidaraan Ekzos Setempat. Sekiranya tiada, alat pernafasan yang sesuai perlu dipakai. Wap kimia yang keluar daripada bahan ini adalah sangat mudah terbakar dan lebih berat daripada jisim udara. Jauhkan daripada sumber nyalaan, percikan, permukaan panas, alat elektrik dan alat pemanasan. Penggunaan alatan kalis api adalah sangat baik sekiranya digunapakai. Alatan dan mesin perlu disambungkan ke wayar bumi untuk mengelakkan pengumpulan cas elektro static. Penyimpanan Simpan di tempat yang mempunyai pengalihan udara yang baik dan tidak terdedah kepada cahaya matahari, sumber nyalaan dan pemanasan. Suhu Simpanan : Suhu Bilik

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

Section 8: Exposure Controls and Personal Protection		Bahagian 8: Kawalan Pendedahan dan Perlindungan Diri	
Occupational Exposure Limits (OEL) This Product consist of a mixture substances with the following recognized or recommended OEL value:		Occupational Exposure Limits(OEL) Produk ini mengandungi campuran bahan-bahan berikut yang mempunyai nilai EOL yang diiktiraf atau disyorkan seperti berikut:	
Chemical Name	TLV	Nama Bahan Kimia	TLV
Toluene	TWA: 50ppm (188mg/m ³)(Skin),ACGIH 2002	Toluene	TWA: 50ppm (188mg/m ³)(Skin),ACGIH 2002
Engineering Control: The use of local exhaust ventilation is recommended to control process emission near the source. Laboratory samples should be handled in a lab hood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.		Kawalan Kejuruteraan : Penggunaan sistem pengalih-udara ekzos setempat adalah digalakkan untuk mengawal proses pembebasan yang berhampiran dengan sumber. Sampel makmal mestilah dikendalikan di dalam kebuk wasap. Sediakan pengalih-udara kalis letupan.	
Personal Protection General Advice: The use and choice of personal protection equipment is related to the hazard of the product, the workplace and the way the product is handled. In general, we recommended as a minimum safety precaution that safety glasses with side-shields and work-clothes protecting arms, legs and body be used. In addition, any person visiting an area where this product is handled should where at least safety glasses with side shields.		Perlindungan Diri Nasihat Umum: Penggunaan dan pemilihan alat perlindungan diri berkaitan dengan bahaya produk, tempat kerja dan cara pengendalian produk. Secara umumnya, alat kawalan keselamatan minimum yang digalakkan penggunaannya adalah seperti kacamata keselamatan dengan penutup sisi, dan pakaian kerja yang melindungi lengan, kaki dan badan. Pelawat yang mengunjungi kawasan di mana bahan ini dikendalikan dan diproses mestilah sekurang-kurangnya memakai kaca mata keselamatan dengan penutup sisi.	
Hand Protection: When handling this product, it is recommended to wear chemical resistant gloves. The choice of suitable protective gloves depends on work conditions and what chemical are handled, but we have positive experience with gloves made of PVA. Note that PVA degrades when in contact with water. Gloves should be replaced immediately if sign of degradation is observed.		Perlindungan Tangan: Sewaktu mengendalikan produk ini, adalah dinasihatkan supaya memakai sarung tangan yang tahan bahan kimia. Pemilihan sarung tangan perlindungan yang sesuai adalah bergantung kepada keadaan ditempat kerja dan jenis bahan kimia yang dikendalikan, tetapi kami mempunyai pengalaman positif bagi sarung tangan jenis PVA. Diingatkan bahawa sarung tangan PVA akan terdegradasi apabila terkena air. sarung tangan perlu diganti dengan segera sekiranya tanda- tanda degradasi dapat diperhatikan.	
Respiratory Protection: Where concentrations in air may exceed the limits given in this section, it is recommended to use a half face filter mask to protect from overexposure by inhalation. Suitable filter material depends on the amount and type of chemical being handled in the workplace. NIOSH Respirator recommendations: NIOSH/OSHA 500 ppm		Perlindungan Pernafasan: Kepekatan bahan ini di dalam udara mungkin melebihi had yang diberikan dalam bahagian ini, maka adalah dinasihatkan untuk memakai topeng penapis keselamatan separuh muka untuk melindungi pendedahan lampau bahan ini melalui pernafasan. Alat penapis sesuai bergantung kepada jumlah dan jenis bahan kimia yang dikendalikan ditempat kerja, tetapi bahan penapis jenis A atau setaraf dengannya boleh digunakan. Topeng penapis yang disyorkan oleh NIOSH: NIOSH/OSHA 500ppm	

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

CCROV*/PAPROV*/GMFOV/SA*/SCBAF:SCBAF:PD,PP/S AF:PD, PP:ASCBA (see symbols and codes) Eye Protection: Refer to general advice Skin/Body Protection: Refer general advice	CCROV*/PAPROV*/GMFOV/SA*/SCBAF:SCBAF:PD,PP/S AF:PD, PP:ASCBA (lihat symbol dan kod) Perlindungan Mata: Rujuk nasihat umum Perlindungan Kulit/Badan Rujuk nasihat umum
Section 9: Physical and Chemical Properties	Bahagian 9: Sifat-sifat Fizikal dan Kimia
Information on basic physical and chemical properties Appearance : Yellowish Liquid Odour : Typical Toluene smell Viscosity : 5000 – 7000 cps Solid content : 23 – 25% Specific Gravity : 0.87 ± 0.02 pH : No Information Boiling Point : No data available Melting Point : No data available Flash Point : -2°C Evaporation rate : No data available Explosive limits : No data available Vapour pressure : No data available Vapour density : No data available Auto ignition temperature : No data available Solubility : Insoluble in water	Maklumat tentang asas fizikal dan sifat kimia Rupa : Cecair Kekuningan Bau : Aromatik Kelikatan : 5000 – 7000 cps Kandungan Pepejal : 23 – 25% Graviti Tertentu : 0.87 ± 0.02 pH : Tiada maklumat Takat didih : Tiada data tersedia Takat lebur : Tiada data tersedia Takat kilat : -2°C Kadar Kemeruawapan : Tiada data tersedia Takat letupan : Tiada data tersedia Tekanan wap : Tiada data tersedia Ketumpatan wap : Tiada data tersedia Takat nyalaan sendiri : Tiada data tersedia Kebolehlarutan : Tak boleh larut dalam air
Section 10: Stability and Reactivity	Bahagian 10: Kestabilan Dan Kereaktifan
Reactivity / Incompatibles Explosive reaction may occur when solvent reacts with concentrated nitric acid, Sulphur dichloride and tetranitromethane. Might react vigorously with strong oxidizing agent. The main polymers in the adhesive are very stable and non-hazardous when dried. Extra precaution should be taken on part of the solvent which act as a carrier and is highly flammable before fully dried.	Keraaktifan / Ketakserasian Reaksi letupan boleh berlaku apabila pelarut bertindak balas dengan asid nitric, sulfur diklorida dan tetranitromethane. Reaksi agresif boleh berlaku jika bercampur dengan agen pengoksidaan. Bahan polimer utama dalam pelekat adalah sangat dan tidak mendatangkan bahaya dalam keadaan kering. Langkah keselamatan hendaklah diambil kerana pelarut yang diguna adalah sangat mudah terbakar sebelum kering.

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

Conditions to avoid Avoid contact with acids. Incompatible materials Material to avoid strong acids. Working area to avoid Confined space. Poor ventilated area. Hazardous polymerization None	Keadaan yang perlu dielakkan Elakkan sentuhan dengan acid. Bahan yang tidak serasi Bahan yang perlu dielakkan asid yang kuat. Kawasan kerja yang perlu dielak Kawasan yang tertutup. Peredaran udara yang kurang baik. Bahaya Polimerisasi Tiada
Section 11: Toxicological Information	Bahagian 11: Maklumat Toksikologi
Information on toxicological effects Inhalation Inhalation is the most significant route of exposure to solvents. May cause respiratory irritation or drowsiness and dizziness, damage to organs through prolonged or repeated exposure and is suspected of damaging fertility or unborn child. Ingestion Ingestion may cause severe irritation of the mouth, the esophagus and the gastrointestinal tract. Skin Contact Cause skin irritation.	Maklumat tentang kesan toksikologi Penyedutan Penyedutan adalah laluan pendedahan yang paling ketara kepada pelarut. Boleh menyebabkan kerengsaan pernafasan atau rasa mengantuk dan pening, kerosakan pada organ melalui pendedahan berpanjangan atau berulang dan disyaki merosakkan kesuburan atau anak dalam kandungan. Pengingesan Boleh membawa maut jika tertelan dan memasuki saluran pernafasan. Sentuhan kulit Menyebabkan kerengsaan kulit.
Section 12: Ecological information	Bahagian 12: Maklumat Ekologi
Ecotoxicity Toxicity: No data available. Persistence and degradability Degradability: No date available. Bio accumulative potential Bio accumulative potential: No date available. Mobility in soil Mobility: Adsorbs to soil and has low mobility. Float on water. Other adverse effects No date available.	Ekotoksikan Ketoksikan: Tiada data tersedia. Ketahanan dan keterdegradasian Kebolehdegradasian: Tiada data tersedia. Potensi bioakumulatif Potensi bioakumulatif: Tiada data tersedia tentang bioakumulasi. Mobiliti dalam tanah Mobiliti: Menyerap ke dalam tanah dan mempunyai mobility yang rendah. Terapung di atas air. Kesan buruk yang lain Tiada data tersedia.

SDS	ELKY E-138	Revision No:	01
		Effective date:	01/10/2025

Section 13: Disposal information	Bahagian 13: Maklumat Pelupusan
Material Disposal Recover or recycle if possible. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water.	Pembuangan Bahan Sisa Guna semula sekiranya boleh. Jangan buang bahan sisa pada alam sekitar, longkang atau laluan air. Jangan benarkan bahan sisa mencemari tanah atau air.
Section 14: Transportation Information	Bahagian 14: Maklumat Pengangkutan
LAND : ADR SEA : IMDG (Packaged goods and BLC's) AIR : (ICAO / IATA) Proper shipping name : Adhesive containing flammable liquid UN No. : UN1133 Hazard Class : 3 Packing Group : III Marine Pollutant : No	TANAH : ADR LAUT : IMDG (Barang bungkusan dan tangki cecair penuh) UDARA : (ICAO / IATA) Proper shipping nama : Adhesive containing flammable liquid Nombor UN : UN1133 Kelas Bahaya : 3 Kumpulan Pembungkusan : III Pencemaran hidupan laut : No
Section 15: Regulatory Information	Bahagian 15: Maklumat Penguatkuasaan
Local Governing Directive : 1. Occupational Safety and Health Act 1994 and Regulations 2. Environmental Quality Act 1975 and Regulations 3. Factories and Machinery Act 1967 and Regulations	Akta Penguatkuasaan Tempatan : 1. Akta Keselamatan dan Kesihatan Pekerjaan 1994 dan Peraturan-Peraturan. 2. Akta Kualiti Alam 1975 dan Peraturan-Peraturan 3. Akta Kilang dan Mesin 1967 dan Peraturan-peraturan
Section 16: Other Information	Bahagian 16: Maklumat lain
The above information is given in good faith and to the best of our knowledge. We make no warranty or guarantee of results and assume no obligation or liability for the use of any product or information mentioned herein. We expect the person(s) receiving this information to exercise their independent judgment or consult with a competent professional to determine the safety and appropriateness of this material for any specific use.	Maklumat di atas adalah diberi dengan keyakinan yang ianya adalah maklumat yang terbaik daripada kami. Kami tidak memberi waranti atau gerenti di atas apa-apa keputusan dan tidak mempunyai tanggungjawab atau liability kepada mana-mana produk atau maklumat yang diberi. Kami harap mereka yang menerima maklumat akan membuat penilaian atau mendapatkan nasihat profesional untuk menentukan tahap keselamatan dan kesesuaian produk bagi kegunaan tertentu.